

CIGWELD

AN ESAB BRAND

CutSkill EasyCut Plasma Cutter



PACKAGE CONTENTS

- CutSkill EasyCut Plasma Power Source
- CutSkill 30A Plasma Torch
- Work Cable and Clamp
- Wrench for Air Filter
- 1 x 1/4" Nitto Air Line Connector
- Operating manual

ORDERING INFORMATION

CutSkill EasyCut Package 1-1601-EC

PARTS & ACCESSORIES

CutSkill Plasma Cutting Tip 0.8mm	CSP337001
CutSkill Plasma Torch Electrode	CSP337003
CutSkill Plasma Torch Standoff Guide	CSP337004
CutSkill Plasma Torch Shield Cup	CSP337005
CutSkill Plasma Torch O-Ring	CSP337006
CutSkill Plasma Torch Gas Diffuser	CSP337007
CutSkill Plasma Inline Filter	CSP337039

CIGWELD

AN ESAB BRAND

CutSkill EasyCut Plasma Cutter



CIGWELD Pty Ltd An ESAB Brand 71 Gower Street, Preston VIC 3072 Australia
Customer Care: Tel: 1300 654 674, Fax: 03 9474 7391, Email: enquiries@cigweld.com.au
International Enquiries: Tel: +61 3 9474 7508 Fax: +61 3 9474 7488

 CIGWELD.COM.AU

WE RECOMMEND GENUINE CIGWELD PRODUCTS

BIGGEST RANGE, BEST QUALITY & GUARANTEED PERFORMANCE



In the interest of continuous improvements, CIGWELD Pty Ltd ABN 56 007 226 815 (An ESAB Brand) reserves the right to change specifications or design on any of its products without prior notice.

 CIGWELD.COM.AU

OUTPUT CURRENT
30A DC

PROTECTION
PART IN PLACE

CLEAN CUT
10mm MILD STEEL
0.8mm TIP

COMPRESSOR REQUIRED
5.3CFM

WARRANTY*
1 YEAR

EasyCut

“No Frills, just serious performance!”

At CIGWELD we aim to develop and deliver on products that bridge the gap in customer requirements.

With the EasyCut we've done just that - a simple, no frills plasma cutter that is not only easy to use but is backed by serious power. Perfectly suited to the DIY cutting user, the EasyCut is still loaded with features - Parts In Place protection to protect your consumables and torch from arc damage, adjustable amperage to suit the plate thickness you're trying to cut, and high grade consumables built for durability saving you time and money!

EASYCUT

- Adjustable amperage
- Parts In Place Protection (PiP)
- Easy to use
- Easy to Cut!

“This little beast packs a punch and is so easy to use!”



REMOVABLE AIR FILTER WITH PURGING VALVE

Moisture in your air compressor can reduce the lifespan of the Plasma Torch consumables. The CutSkill inbuilt air filter removes this problem. The air filter can be purged at any time by using the purging valve and is also removable for cleaning. It is housed in a concave inset in order to prevent damage.

INTERNAL REGULATOR

The regulator is internal and air through the torch is managed automatically by the plasma unit. This removes the need to adjust air pressure for individual cutting requirements.

TORCH

The EasyCut Plasma Cutter comes complete with a direct connected 30Amp torch with a 4m lead for greater reach, comfort and ergonomics designed specifically for the CutSkill plasma cutting range. The torch includes a safety latch in order to prevent risk of accidental arc.

CONSUMABLES

Using the same high grade consumables as the CutSkill 35 you can rest easy knowing you're getting the very best quality and longevity from your consumables.

FEATURES

- 30A DC** Output Current
Current range for this Power Source is 15-30A. Provides DC Output.
- In-Built Regulator**
In-Built Pre Calibrated Regulator to ensure optimal air pressure for superior cutting performance.
- Removable Air Filter with Purging Valve**
Designed to filter and purge any air contaminants, increasing consumables lifespan. Removable for easy cleaning and cleverly installed flush to rear panel to prevent damage. *For optimal filtration, an Inline Filter is recommended P/N: CSP337039.
- Parts In Place (PIP) Protection**
If the torch consumables are not correctly installed the torch will not arc, increasing the lifespan of the consumables and torch itself.
- Cutting**
10mm Genuine Cut, Mild Steel, Aluminium & Stainless Steel.
12mm Severance Cut, Mild Steel, Aluminium & Stainless Steel.
8mm Pierce Cut.
- Generator**
Recommended generator required:
7.5kVA at 0.8 Power Factor.
- Air Compressor**
Recommended air compressor required:
800kPa, 5.3 CFM.
- AS** Fully Compliant to AS 60974.1-2006.
Enclosure rated to IP21S.
- 1 YEAR*** 1 Year Limited Warranty*
*Refer to operating manual for further details.

ACCESSORIES

Inline Air Filter

The inline Air Filter is designed to prevent all moisture, plus oil and dirt down to 0.85 microns from passing through your air line to the plasma unit. This offers extra protection in addition to the inbuilt air filter located in the plasma unit itself.

Circle Cutting Guide


The Circle Cutting Guide allows for circle cutting up to a radius of 400mm. The cutting guide can be affixed to the work plate by either of the included Straight, Magnetic or Screw Pivots.

WARRANTY

1-Year Warranty on the power source.

PARTS IN PLACE (PIP) PROTECTION

If the torch consumables are not correctly installed the torch will not arc, increasing the lifespan of the consumables and torch itself.



SPECIFICATIONS

	GENUINE CUT: MILD STEEL, STAINLESS STEEL & ALUMINIUM	10mm
	SEVERANCE CUT: MILD STEEL, STAINLESS STEEL & ALUMINIUM	12mm
	PIERCE CUT:	8mm
	INPUT POWER:	240V, 1Ph, 10A
	30A 15% DUTY CYCLE:	15% @ 30A
	CURRENT RANGE:	15-30Amps
	kPa INPUT AIR REQUIRED:	800kPa, 150LPM
	GENERATOR REQUIRED:	7.5kVA
	DIMENSIONS:	380mm L x 175mm W x 325mm H
	WEIGHT:	10.5kg